



1. Product and company identification

| | |
|--------------------------------------|--|
| Product name | Castrol Dex/Merc Domestic Multi-vehicle ATF |
| MSDS # | 465367 |
| Code | 465367-CA01 |
| Product use | Automatic transmission fluid. For specific application advice see appropriate Technical Data Sheet or consult our company representative. |
| Manufacturer | BP Lubricants USA, Inc 1500 Valley Road Wayne, NJ USA 07470 |
| Supplier | Wakefield Canada, Limited 3620 Lakeshore Blvd West Toronto, Ontario, Canada M8W 1P2 Phone Number - 416-252-5511 Fax Number - 416-252-7315 BP Lubricants USA, Inc 1500 Valley Road Wayne, NJ USA 07470 Phone Number - 973-633-2296 Fax Number - 973-633-7475 |
| EMERGENCY HEALTH INFORMATION: | 1 (800) 447-8735 Outside the US: +1 703-527-3887 (CHEMTREC) |
| EMERGENCY SPILL INFORMATION: | 1 (800) 424-9300 CHEMTREC (USA) |
| OTHER PRODUCT INFORMATION | 1 (866) 4 BP - MSDS (866-427-6737 Toll Free - North America) email: bpcares@bp.com |

2. Hazards identification

| | |
|---------------------------------|--|
| Physical state | Liquid. |
| Color | Red. |
| Emergency overview | CAUTION ! MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION. Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. |
| Routes of entry | Dermal contact. Eye contact. Inhalation. |
| Potential health effects | |
| Eyes | May cause eye irritation. |

| | | |
|---|---------------------------------|-------------------------|
| Product name Castrol Dex/Merc Domestic Multi-vehicle ATF | Product code 465367-CA01 | Page: 1/6 |
| Version 5 Date of issue 12/03/2015. | Format Canada | Language ENGLISH |
| | (Canada) | (ENGLISH) |

| | |
|-------------------|---|
| Skin | May cause skin irritation. |
| Inhalation | May cause respiratory tract irritation. |
| Ingestion | Ingestion may cause gastrointestinal irritation and diarrhea. |

See toxicological information (Section 11)

3. Composition/information on ingredients

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

| Ingredient name | CAS # | % |
|---------------------------|-----------------------------------|---------|
| Base oil - highly refined | Varies - See Key to abbreviations | 80 - 85 |
| Base oil - highly refined | Varies - See Key to abbreviations | 15 - 20 |

4. First aid measures

| | |
|---------------------------|---|
| Eye contact | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if symptoms occur. |
| Skin contact | Immediately wash exposed skin with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur. |
| Inhalation | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention. |
| Ingestion | Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If potentially dangerous quantities of this material have been swallowed, call a physician immediately. Get medical attention if symptoms occur. |
| Notes to physician | Treatment should in general be symptomatic and directed to relieving any effects. |

5. Fire-fighting measures

| | |
|--------------------------------------|---|
| Flash point | <input checked="" type="checkbox"/> Closed cup: >200°C (>392°F) [Pensky-Martens.] <input type="checkbox"/> Open cup: 190°C (374°F) [Cleveland.] |
| Fire/explosion hazards | In a fire or if heated, a pressure increase will occur and the container may burst. |
| Extinguishing media | |
| Suitable | Use an extinguishing agent suitable for the surrounding fire. |
| Not suitable | Do not use water jet. |
| Fire-fighting procedures | Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. |
| Hazardous combustion products | Combustion products may include the following: carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide) |
| Protective clothing (fire) | Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. |

6. Accidental release measures

| | |
|----------------------------------|---|
| Personal precautions | No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8). |
| Environmental precautions | Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). |
| Methods for cleaning up | |

| | | | | |
|---------------------|---|----------------------|-------------------------|------------------|
| Product name | Castrol Dex/Merc Domestic Multi-vehicle ATF | Product code | 465367-CA01 | Page: 2/6 |
| Version 5 | Date of issue 12/03/2015. | Format Canada | Language ENGLISH | |
| | | (Canada) | (ENGLISH) | |

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Small spill

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

7. Handling and storage

Handling

Put on appropriate personal protective equipment (see Section 8). Workers should wash hands and face before eating, drinking and smoking. Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate.

Storage

Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Not suitable

Prolonged exposure to elevated temperature

8. Exposure controls/personal protection

Occupational exposure limits

Ingredient name

Base oil - highly refined

Occupational exposure limits

CA Alberta Provincial (Canada).

15 min OEL: 10 mg/m³ 15 minutes. Issued/Revised: 7/2009 Form: Mist

8 hrs OEL: 5 mg/m³ 8 hours. Issued/Revised: 4/2004 Form: Mist

CA Quebec Provincial (Canada).

STEV: 10 mg/m³ 15 minutes. Issued/Revised: 1/2000 Form: mist

TWAEV: 5 mg/m³ 8 hours. Issued/Revised: 1/2000 Form: mist

CA Ontario Provincial (Canada).

TWA: 5 mg/m³ 8 hours. Issued/Revised: 1/1992 Form: mist

STEL: 10 mg/m³ 15 minutes. Issued/Revised: 1/1992 Form: mist

Base oil - highly refined

CA Alberta Provincial (Canada).

15 min OEL: 10 mg/m³ 15 minutes. Issued/Revised: 7/2009 Form: Mist

8 hrs OEL: 5 mg/m³ 8 hours. Issued/Revised: 4/2004 Form: Mist

CA Quebec Provincial (Canada).

STEV: 10 mg/m³ 15 minutes. Issued/Revised: 1/2000 Form: mist

TWAEV: 5 mg/m³ 8 hours. Issued/Revised: 1/2000 Form: mist

CA Ontario Provincial (Canada).

TWA: 5 mg/m³ 8 hours. Issued/Revised: 1/1992 Form: mist

STEL: 10 mg/m³ 15 minutes. Issued/Revised: 1/1992 Form: mist

While specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Control Measures

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

Product name Castrol Dex/Merc Domestic Multi-vehicle ATF

Product code 465367-CA01

Page: 3/6

Version 5 **Date of issue** 12/03/2015.

Format Canada

Language ENGLISH

(Canada)

(ENGLISH)

Personal protection

| | |
|----------------------|---|
| Eyes | Avoid contact with eyes. Safety glasses with side shields or chemical goggles. |
| Skin and body | Avoid contact with skin and clothing. Wear suitable protective clothing. |
| Respiratory | Use adequate ventilation. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. |
| Hands | <p>The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.</p> <p>Consult your supervisor or Standard Operating Procedure (S.O.P) for special handling instructions.</p> |

9. Physical and chemical properties

| | |
|------------------------------|---|
| Physical state | Liquid. |
| Color | Red. |
| Odor | Not available. |
| Odor threshold | Not available. |
| Flash point | ☑ Closed cup: >200°C (>392°F) [Pensky-Martens.] Open cup: 190°C (374°F) [Cleveland.] |
| Specific gravity | Not available. |
| Density | 855 kg/m ³ (0.855 g/cm ³) at 15°C |
| pH | Not available. |
| Viscosity | ☑ Kinematic: 33.5 mm ² /s (33.5 cSt) at 40°C Kinematic: 7.54 mm ² /s (7.54 cSt) at 100°C |
| Boiling point / Range | Not available. |
| Melting point / Range | Not available. |
| Vapor pressure | Not available. |
| Vapor density | Not available. |
| Evaporation rate | Not available. |
| Solubility | insoluble in water. |
| LogK_{ow} | Not available. |

10. Stability and reactivity

| | |
|--|--|
| Stability and reactivity | The product is stable. |
| Possibility of hazardous reactions | Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | Avoid all possible sources of ignition (spark or flame). |
| Incompatibility with various substances | Reactive or incompatible with the following materials: oxidizing materials. |
| Hazardous decomposition products | Under normal conditions of storage and use, hazardous decomposition products should not be produced. |
| Hazardous polymerization | Under normal conditions of storage and use, hazardous polymerization will not occur. |

11. Toxicological information

Potential chronic health effects

| | |
|-----------------------------|---|
| Carcinogenicity | No known significant effects or critical hazards. |
| Mutagenicity | No known significant effects or critical hazards. |
| Teratogenicity | No known significant effects or critical hazards. |
| Fertility effects | No known significant effects or critical hazards. |
| Reproductive effects | No known significant effects or critical hazards. |

Medical conditions aggravated by over-exposure None known.

12. Ecological information

Ecotoxicity

No testing has been performed by the manufacturer.

| | |
|-------------------------------------|--|
| Persistence/degradability | Expected to be biodegradable. |
| Mobility | Spillages may penetrate the soil causing ground water contamination. |
| Bioaccumulative potential | This product is not expected to bioaccumulate through food chains in the environment. |
| Other ecological information | Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired. |

13. Disposal considerations

Waste information The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

NOTE: The generator of waste has the responsibility for proper waste identification (based on characteristic(s) or listing), transportation and disposal

14. Transport information

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)

15. Regulatory information

WHMIS (Canada) Not controlled under WHMIS (Canada).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Other regulations

Canada inventory All components are listed or exempted.

United States inventory (TSCA 8b) All components are listed or exempted.

| | | | |
|---|----------------------------------|----------------------|-------------------------|
| Product name Castrol Dex/Merc Domestic Multi-vehicle ATF | Product code 465367-CA01 | Page: 5/6 | |
| Version 5 | Date of issue 12/03/2015. | Format Canada | Language ENGLISH |
| | | (Canada) | (ENGLISH) |

| | |
|--------------------------------------|---|
| REACH Status | For the REACH status of this product please consult your company contact, as identified in Section 1. |
| Australia inventory (AICS) | All components are listed or exempted. |
| China inventory (IECSC) | All components are listed or exempted. |
| Japan inventory (ENCS) | All components are listed or exempted. |
| Korea inventory (KECI) | All components are listed or exempted. |
| Philippines inventory (PICCS) | All components are listed or exempted. |
| Taiwan inventory (CSNN) | All components are listed or exempted. |

16. Other information

Label requirements CAUTION !
MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION.

History

Date of issue 12/03/2015.

Date of previous issue 12/02/2015.

Prepared by Product Stewardship

Key to abbreviations Varies = may contain one or more of the following 101316-69-2, 101316-70-5, 101316-71-6, 101316-72-7, 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64741-97-5, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-64-9, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1, 74869-22-0, 90669-74-2

Notice to reader

 **Indicates information that has changed from previously issued version.**

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.