8000 SERIES

METAL CONDITIONER

DESCRIPTION AND USES

METALPRO 8000 Series metal conditioner is specifically formulated to comply with VOC Regulations. A high-performance combination of phosphoric acid and water-soluble detergent, it removes fat, oxidation and light rust all at the same time and provides a thin layer of phosphate to improve paint adhesion. Can be use on steel, galvanized steel and aluminum.

** In accordance with existing Canadian Regulations on Volatile Organic Compounds (SOR / 2009-264 and SOR / 2009-197).*

TECHNICAL DATA

Colour	clear	**Packaging**	1 l, 3.78 l et 18.9 l
Physical state	liquid	**Shelf life**	12 months @ 25 °C (77 °F)
pH	1 to 2	**Odor**	pungent
Density	1.185 ± 0.05 kg/l	**VOC**	40g/l (< 0.35 lb/gal U.S.)

APPLICATION

METALPRO metal conditioner is ready to use and requires no dilution or pre-mixing.

Hand spray the product on metal surface and wait 2 minutes. Be careful not to let dry. Rinse with water and wipe with a dry cloth. Wait at least half an hour before applying the paint.

IMPORTANT

Product must be used only in accordance with the information in this data sheet, the information indicated on the labels and on the Safety Data Sheet.

See the Safety Data Sheet and the product label for more information on safety and precautions requirements. Keep away from open flame or sparks. Flammable

Notice: *UAP inc. does not offer any implied or express warranties of any kind with respect to the performance, life, adhesion or covering power of its products as it has no control over the manner or conditions in which its products are and will be used. The information in this data sheet is provided in good faith and is subject to change without notice. For additional information, contact your representative*